

Lgns(s)

TWO-AXLE FLAT WAGON FOR TRANSPORTING CONTAINERS AND MOBILE CRATES



Wagon Use:

Transporting:

- one 40-foot container or two 20-foot containers
- one 20-foot or one 30-foot container, centred
- Swap bodies of appropriate length

Wagon superstructure:

Each wagon is fitted with the necessary pegs for centering/locking containers in place. The wagons can also be used for transporting swap bodies of appropriate dimensions.

General

| code | Lgns(s) | | | |
|----------------------|-----------|---------------|---------------|---------------|
| Type | | 6449A0 | 6450A0 | 6451A0 |
| Number Available | | 100 | 200 | 60 |
| Wagon number | code | 23 88 | 23 88 | 23 88 |
| series | - from | 4439 000 - a | 4439 100 - a | 4432 500 - a |
| | - to | 4439 099 - a | 4439 299 - a | 4432 559 - a |
| Year of construction | | 1999 | 2000 | 1990 |

Dimension (in mm)

| | | | | |
|------------------------|-----------|--------|--------|--------|
| Overall length | LW | 13 860 | 15 090 | 13 860 |
| Distance between axles | A | 9 000 | | |
| Overall width | BW | 2 930 | | |
| Floor height | HP | 1 175 | | |
| Usable length | L | 12 620 | 13 800 | 12 620 |

Weight (in t)

| | | | |
|-----------|------|------|--------------|
| Mean tare | 11,7 | 12,5 | 12,0 (*12,4) |
|-----------|------|------|--------------|

* with hand brakes

Type 6449A0

Authorised load (in t)


| | A | B | C | D |
|----|------|------|------|------|
| S | 20,3 | 24,3 | 28,3 | 33,3 |
| SS | 20,3 | 24,3 | 28,3 | |

Type 6450A0

Authorised load (in t)

| | A | B | C | D |
|----|------|------|------|------|
| S | 19,5 | 23,5 | 27,5 | 32,5 |
| SS | 19,5 | 23,5 | 27,5 | |

Special Markings
6449A0 / 6450A0 / 6451A0



Type 6451A0

Authorised load (in t)

| | A | B | C | D |
|----|------|------|------|------|
| S | 20,0 | 24,0 | 29,0 | 33,0 |
| SS | 0,00 | | | |

**

-0,4 with hand brakes